

Please email technical assistance, support@gtogrilles.com, if you require assistance beyond the scope of these instructions.

Professional finishing and installation is highly recommended.

ATTENTION

THE FOLLOWING CONTAINS IMPORTANT INFORMATION REGARDING PAINTING OF THE URETHANE PIECES.

IT IS IMPERATIVE THAT THESE STEPS BE FOLLOWED IN ORDER TO AVOID ANY PROBLEMS WITH THE PAINT.

IF THESE INSTRUCTIONS ARE NOT FOLLOWED, YOU MAY EXPERIENCE PEELING, CHIPPING, AND/OR BUBBLING OF THE PAINT.

PAINTING INSTRUCTIONS

1. Pre-fit parts to vehicle. Follow included installation instructions.
2. All painted surfaces must be sanded with 150 grit paper. This is very important as the primer requires a rough surface for proper adhesion. Ensure that every surface where you want the paint to stick is thoroughly sanded.
3. Clean all surfaces with a solution of HOT water and dish soap.
4. Clean all surfaces with acetone.
5. Clean all surfaces with a wax and grease remover.
6. Prime with high quality urethane primer with a flex additive.
7. Putty any pinholes.
8. Re-prime is necessary.
9. Pre-fit parts to vehicle.
10. Thoroughly hand sand with 320 grit sand paper. Ensure that every surface where you want the paint to stick is thoroughly sanded.
11. Clean with wax and grease remover.
12. Paint-add flex additive to the paint.