

Estimated Installation Time: 30 Minutes

Supplies and tools required

- Floor jack
- Jack stands
- Electric drill with 1/8" and 5/16" drill bits
- Phillips screwdriver
- 4mm Allen key or socket
- 7/16" wrench or socket
- Container for holding fasteners removed from vehicle
- Blanket or other objects to lay under front of vehicle to prevent bumper damage while removed (if you remove the bumper).
- C-Clamps

1. Read through these instructions completely from start to finish before proceeding.
2. Raise the front of the car. This can be done with ramps, jackstands or a lift. Consult your owners manual for information about locations for jacks and jack stands. Raise the car high enough to fit your power drill with a drill bit attached underneath. An alternate method is to remove the front bumper.
3. Clamp the splitter to the bottom of the bumper, with the textured side up. Move the splitter so the back edge butts up against the flange on the bottom of the bumper. Center it from side to side on the bumper. Finalize the position of the splitter at this time.
4. Place a mark at the front of the slots in the splitter on the bottom of the bumper. This will allow you to slide the splitter forward once installed if adjustment is desired.
5. Drill 1/8" pilot holes centered in the slot on each marked location.
6. Remove the splitter and enlarge the holes to 5/16". You may find that 3/8" holes work better, but this should only be done if absolutely necessary.
7. Mount the splitter to the bottom of the bumper. To do this, start in the middle and work toward the sides. Each hole will need one bolt, two washers and one nylock nut. Install one washer under the bolt head and one washer under the nut. The bolt head should be underneath the bumper and the nut should be on top. Start all of the fasteners by hand.
8. Ensure that the splitter is positioned where you want it and tighten all the hardware.
9. Lower the car to the ground, and enjoy!
10. Email pictures of your car to sales@gtogrilles.com!

This product is for appearance purposes ONLY. This product is not intended, in any way, to be used as an actual aerodynamic enhancement piece. GTO Grilles assumes no responsibility for any damage caused to the product, or the vehicle it is installed upon, from misuse or improper installation.